



NAVY ENCLOSURE 100-CS-169

Features

Physical - can all be customized*

Dimensions:	59 x 24 x 32 (H x W x D)
Weight:	473 lbs (with printers).
Shock & Vibration:	Externally Isolated
Material:	Steel construction
Payload:	125 lbs

Installation - can all be customized*

Vessel Interface:	Base and Rear Mounted
Equipment:	HP LaserJet 4600n color LaserJet HP 3320n mfp LaserJet
I/O:	Rear 4in x 4in cutout
Hatch entry/narrow passageway:	No disassembly required

Configuration - can all be customized*

Removable side panels:	Interchangeable
Access to equipment:	Front, rear and sides
Extended slides (lockout):	150 lbs per tray
Door opening:	Left or right swing, hinge out
Lockout, two positions:	120o

Installed Equipment

Power distribution:	Hard wired to Terminal block
Air cooling:	Louvered front, rear and sides
Drawers:	1U slide mounted
Cable management:	Pivoted cable retractors

Based on program requirements



Environmental Characteristics

Shock:	MIL-S-901D Grade A, Heavy weight
Vibration:	MIL STD 167-1
Sand/Dust, Salt/Fog, Spill/Rain:	IP56

901D Rackable Options

Cooling	PDU / FMU	UPS	PCU
VME/cPCI chassis	Drawers or Slides	FPD [LCD]	FPD [Plasma]
Keyboard / Display / KVM	Ethernet Media Converter / Switch	Extended Temperature Range	

All Features, Environmental Characteristics and Options can be customized to your program requirements *