



NAVY ENCLOSURE 2080-S-D01023

Features

Physical - can all be customized*

Standard

| | |
|--------------------------------|-----------------------|
| Dimensions (with stabilizers): | 72" H x 24" W x 32" D |
| Weight: | 450 lbs. |
| U's available: | 36U |
| Shock & Vibration: | Externally isolated |
| Material: | Steel |
| Payload: | Up to 600 lbs |

Installation - can all be customized*

| | |
|-------------------|---|
| Vessel Interface: | Drop-in placement for xxxxx dual stage rack |
| Equipment: | 19" EIA hole pattern front and back |
| I/O: | Through sectional rear panels |

Configuration - can all be customized*

| | |
|------------------------|---------------------------------|
| Removable side panels: | Louvered back panels |
| Equipment mounting: | Universal side mounting bracket |
| Grounding: | Bus bar, ground stud |

Options Installed - can all be customized*

| | |
|---------------------|----------------------------------|
| Power distribution: | 6 channel PDU |
| UPS: | 2 KVA UPS |
| Air cooling: | 1.5 KW fan tray |
| Drawers: | 1U slide mounted with shock pins |
| Cable management: | Pivoted cable retractors |



Environmental Characteristics

| | |
|-------------|----------------------------------|
| Shock : | MIL-S-901D Grade A, Heavy weight |
| Vibration : | MIL-STD -167-1 |

901D Rackable Options

| | | | |
|--------------------------|-----------------------------------|----------------------------|----------------|
| Cooling | PDU / FMU | UPS | PCU |
| VME/cPCI chassis | Drawers or Slides | FPD [LCD] | FPD [Plasma] |
| Keyboard / Display / KVM | Ethernet Media Converter / Switch | Extended Temperature Range | |

All Features, Environmental Characteristics and Options can be customized to your program requirements*