



NAVY MISSION CRITICAL ENCLOSURE 300-CS-147

Features

Physical - can all be customized*

Dimensions:	72" H x 28" W x 32"D
Weight:	560 lbs.
U's available:	36U
Shock & Vibration:	Internally isolated
Material:	Steel construction

Installation - can all be customized*

Vessel interface:	Base mounted
Equipment:	19" EIA hole pattern
I/O:	Top, rear on base
Cable management:	Pivoted retractor
Hatch entry/narrow passageway:	No disassembly of equipment required

Configuration - can all be customized*

Removable side panels:	Interchangeable
Access to equipment:	Front, rear and sides
Extended slides (lockout):	250 lbs capacity per tray
Door opening:	Left or right swing, hinge out

Options Installed - can all be customized*

Power distribution:	1x 6 channels 1U PDU
UPS:	1x 2 KVA UPS
Air cooling:	1x 2 KW fan tray
Drawers:	10 x 1U slide mounted with shock pins
Cable management:	10 x Pivoted cable retractors



Environmental Characteristics

Shock:	MIL-S-901D Grade A, Heavy weight
Vibration:	MIL STD 167-1
EMI/RFI:	MIL-STD 461D
Sand/Dust, Salt/Fog, Spill/Rain:	MIL-STD 810E

901D Rackable Options

Cooling	PDU / FMU	UPS	PCU
VME/cPCI chassis	Drawers or Slides	FPD [LCD]	FPD [Plasma]
Keyboard / Display / KVM	Ethernet Media Converter / Switch	Extended Temperature Range	

All Features, Environmental Characteristics and Options can be customized to your program requirements*