



NAVY ENCLOSURE 300-CS-216

Features

Physical - can all be customized*

Dimensions:	63 1/2" H x 22" W x 31 1/2" D
Weight:	510lbs.
U's available:	36U
Shock & Vibration:	Internally isolated - patent pending
Material:	Steel construction
Payload:	Up to 800 lbs.

Installation - can all be customized*

Vessel Interface:	Base mounted
Equipment:	19" EIA hole pattern
I/O:	Per program requirements
Hatch entry/narrow passageway:	No disassembly required

Configuration - can all be customized*

Access to equipment:	Front
Extended slides (lockout):	250lbs capacity per tray
Door opening:	Split Left and Right swing, hinge out

Options Installed - can all be customized*

Air cooling:	300cfm fan tray
Drawers:	1U slide mounted with shock pins
Cable management:	Pivoted cable retractors



Environmental Characteristics

Shock:	MIL-S-901D Grade A, Heavy weight
Vibration:	MIL-STD-167-1
EMI/RFI:	MIL-STD-461D
Sand/Dust, Salt/Fog, Spill/Rain:	MIL-STD-810E
Airborne Noise:	MIL-STD-740

901D Rackable Options

Cooling	PDU / FMU	UPS	PCU
VME/cPCI chassis	Drawers or Slides	FPD [LCD]	FPD [Plasma]
Keyboard / Display / KVM	Ethernet Media Converter / Switch	Extended Temperature Range	

All Features, Environmental Characteristics and Options can be customized to your program requirements*