



RUGGED KEYBOARD P/N KEY-RM-16X

901D rugged keyboard is fitted with a 1 3/8" Trackball and can be mounted in a variety of configurations including Desktop, Rackmount (1U) and Boltdown. It is extremely resistant to adverse environmental conditions, including shipboard applications and is particularly well suited for military applications.



Features

Size	16.92" (429.78mm) width x 8.56" (217.42mm) depth x 1.46" (36.97mm) height. Note: Dimensions do not include connector, optional feet, cable, flange mount, or wrist rest when supplied
Weight	5.4 lbs. (2.5 kg)
Switches	Full Travel (0.150"/3.81mm); >100 million cycles; Total: 121 (118 keyboard keyswitches & 3 trackball buttons/switches)
Power	Keyboard logic: +5 volts DC @ 250 mA max
Temperature	Operating: -20°C (-4°F) to +70°C (+158°F); Non-Operating: -40°C (-40°F) to +70°C (+158°F)
Humidity	0 to 95% rh, non-condensing
EMI/RFI	Designed to meet FCC Class B
Rain/Spill	MIL-STD-810
Sand/Dust	MIL-STD-810
Altitude	+35,000 feet (+10,000 m)
Shock	MIL-STD-810, 30g
Vibration	MIL-STD-810, 5g, 4 to 33 Hz
Safety	UL Recognized (File #E179526)
MTBF	> 9000 hour

901D Options

- Shock Protection to MILS-901D (100 g)
- Stainless Steel Casing
- Fully Sealed Housing (can be dropped in water)